



*Document Version: 1.4*

*Date: 2006/2/28*

## **Product Specifications**

**26.0" WXGA Color TFT-LCD Module**  
**Model Name: T260XW02 V4**

**( ) Preliminary Specifications**

**(\*) Final Specifications**



## Contents

| No  | ITEM                         |
|-----|------------------------------|
|     | COVER                        |
|     | CONTENTS                     |
|     | RECORD OF REVISIONS          |
| 1   | GENERAL DESCRIPTION          |
| 2   | ABSOLUTION MAXIMUM RATINGS   |
| 3   | ELECTRICAL SPECIFICATIONS    |
| 3-1 | ELECTRICAL CHARACTERISTICS   |
| 3-2 | INTERFACE CONNECTIONS        |
| 3-3 | SIGNAL TIMING SPECIFICATIONS |
| 3-4 | SIGNAL TIMING WAVEFORMS      |
| 3-5 | COLOR INPUT DATA REFERENCE   |
| 3-6 | POWER SEQUENCE               |
| 4   | OPTICAL SPECIFICATIONS       |
| 5   | MECHANICAL CHARACTERISTICS   |
| 6   | RELIABILITY                  |
| 7   | INTERNATIONAL STANDARDS      |
| 7-1 | SAFETY                       |
| 7-2 | EMC                          |
| 8   | PACKING                      |
| 9   | PRECAUTIONS                  |



## Record of Revision

| Version | Date      | No | Old Description  | New Description                                    | Remark  |
|---------|-----------|----|------------------|----------------------------------------------------|---------|
| 1.0     | 7/12 '05  |    | Original version |                                                    |         |
| 1.1     | 10/11 '05 |    | First release    |                                                    |         |
| 1.2     | 12/15 '05 |    | Timing update    |                                                    |         |
| 1.3     | 1/17 '06  |    |                  | Modify inverter mylar shielding screw hole portion | p.20~21 |
| 1.4     | 2/28 '06  |    | Timing table     | Add recommend maximum rating                       | p.11    |
|         |           |    |                  |                                                    |         |
|         |           |    |                  |                                                    |         |
|         |           |    |                  |                                                    |         |
|         |           |    |                  |                                                    |         |



## 1. General Description

This specification applies to the 26.0 inch Color TFT-LCD Module T260XW02. This LCD module has a TFT active matrix type liquid crystal panel 1366x768 pixels, and diagonal size of 26.0 inch. This module supports 1366x768 XGA-WIDE mode (Non-interlace).

Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 8-bit gray scale signal for each dot.

The T260XW02 has been designed to apply the 8-bit 1 channel LVDS interface method. It is intended to support displays where high brightness, wide viewing angle, high color saturation, and high color depth are very important.

### \* General Information

| Items              | Specification                   | Unit   | Note          |
|--------------------|---------------------------------|--------|---------------|
| Active Screen Size | 26.0                            | inches |               |
| Display Area       | 575.769 (H) x 323.712(V)        | mm     |               |
| Pixel Pitch        | 0.4215                          | mm     |               |
| Outline Dimension  | 626.0 (H) x 373.0 (V) x 43.3(D) | mm     | With inverter |
| Driver Element     | a-Si TFT active matrix          |        |               |
| Display Colors     | 16.7M                           | Colors |               |
| Number of Pixels   | 1366 x 768                      | Pixel  |               |
| Pixel Arrangement  | RGB vertical stripe             |        |               |
| Display Mode       | Normally Black                  |        |               |
| BL Structure       | 8 U-Lamps                       |        |               |
| Surface Treatment  | AG, 3H                          |        |               |


## 2. Absolute Maximum Ratings

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

| Item                           | Symbol | Min  | Max  | Unit   | Conditions |
|--------------------------------|--------|------|------|--------|------------|
| Logic/LCD Drive Voltage        | VDD    | -0.3 | 13.2 | [Volt] | Note 1     |
| Input Voltage of Signal        | Vin    | -0.3 | 3.6  | [Volt] | Note 1     |
| BLU Input Voltage              | VDDDB  | -0.3 | 27.0 | [Volt] | Note 1     |
| BLU Brightness Control Voltage | BLON   | -0.3 | 6.0  | [Volt] | Note 1     |
| Operating Temperature          | TOP    | 0    | +50  | [°C]   | Note 2     |
| Operating Humidity             | HOP    | 10   | 90   | [%RH]  | Note 2     |
| Storage Temperature            | TST    | -20  | +60  | [°C]   | Note 2     |
| Storage Humidity               | HST    | 10   | 90   | [%RH]  | Note 2     |

Note 1 : Duration = 50msec

Note 2 : Maximum Wet-Bulb should be 39°C and No condensation.





### 3. Electrical Specification

The T260XW02 requires two power inputs. One is employed to power the LCD electronics and to drive the TFT array and liquid crystal. The second input power for the BLU, is to power inverter..

#### 3-1 Electrical Characteristics

| Parameter                   | Symbol            | Values |        |      | Unit              | Notes |
|-----------------------------|-------------------|--------|--------|------|-------------------|-------|
|                             |                   | Min.   | Typ.   | Max. |                   |       |
| LCD:                        |                   |        |        |      |                   |       |
| Power Supply Input Voltage  | V <sub>CC</sub>   | 10.8   | 12.0   | 13.2 | V <sub>DC</sub>   |       |
| Power Supply Input Current  | I <sub>CC</sub>   | -      | 583    | 682  | mA                | 1     |
| Power Consumption           | P <sub>C</sub>    | -      | 7.0    | 9.0  | Watt              | 1     |
| Inrush Current              | I <sub>RUSH</sub> | -      | -      | 3.0  | A <sub>peak</sub> | 2     |
| Backlight Power Consumption |                   |        | 72     | 81.6 | Watt              |       |
| Life Time                   |                   | 50,000 | 60,000 |      | Hours             | 3     |

**Note :**

1. V<sub>CC</sub>=12.0V,  $f_v = 60\text{Hz}$ ,  $f_{CLK} = 81.0\text{ MHz}$ , 25°C.
2. Duration = 470 ms
3. The performance of the Lamp in LCM, for example: lifetime or brightness, is extremely influenced by the characteristics of the DC-AC Inverter. So all the parameters of an inverter should be carefully designed so as not to produce too much leakage current from high-voltage output of the inverter. When you design or order the inverter, please make sure unwanted lighting caused by the mismatch of the lamp and the inverter (no lighting, flicker, etc) never occurs. When you confirm it, the LCD Assembly should be operated in the same condition as installed in your instrument.
4. Do not attach a conducting tape to lamp connecting wire. If the lamp wire attach to conducting tape, TFT-LCD Module have a low luminance and the inverter has abnormal action because leakage current occurs between lamp wire and conducting tape.
5. The relative humidity must not exceed 80% non-condensing at temperatures of 40°C or less. At temperatures greater than 40°C, the wet bulb temperature must not exceed 39°C. When operate at low temperatures, the brightness of CCFL will drop and the lifetime of CCFL will be reduced.



### 3-2 Interface Connections

- LCD connector (CN1): FI-X30SSL-HF (JAE) or equivalent
- Mating Connector: FI-X30H (JAE), FI-X30HL (JAE-Lock type) or equivalent
- LVDS Transmitter: SN75LVDS83(Texas Instruments) or equivalent

**Note:**

1. All GND (ground) pins should be connected together and should also be connected to the LCD's metal frame. All Vcc (power input) pins should be connected together.


| Pin No | Symbol      | Description                              | Default           |
|--------|-------------|------------------------------------------|-------------------|
| 1      | VCC         | +12V, DC, Regulated                      |                   |
| 2      | VCC         | +12V, DC, Regulated                      |                   |
| 3      | VCC         | +12V, DC, Regulated                      |                   |
| 4      | VCC         | +12V, DC, Regulated                      |                   |
| 5      | GND         | Ground and Signal Return                 |                   |
| 6      | GND         | Ground and Signal Return                 |                   |
| 7      | GND         | Ground and Signal Return                 |                   |
| 8      | GND         | Ground and Signal Return                 |                   |
| 9      | LVDS Option | Low/Open for Normal (NS), High for JEIDA | Option            |
| 10     | Reserved    | Open or High                             | AUO internal test |
| 11     | GND         | Ground and Signal Return for LVDS        |                   |
| 12     | RXIN0-      | LVDS Channel 0 negative                  |                   |
| 13     | RXIN0+      | LVDS Channel 0 positive                  |                   |
| 14     | GND         | Ground and Signal Return for LVDS        |                   |
| 15     | RXIN1-      | LVDS Channel 1 negative                  |                   |
| 16     | RXIN1+      | LVDS Channel 1 positive                  |                   |
| 17     | GND         | Ground and Signal Return for LVDS        |                   |
| 18     | RXIN2-      | LVDS Channel 2 negative                  |                   |
| 19     | RXIN2+      | LVDS Channel 2 positive                  |                   |
| 20     | GND         | Ground and Signal Return for LVDS        |                   |
| 21     | RXCLKIN-    | LVDS Clock negative                      |                   |
| 22     | RXCLKIN+    | LVDS Clock positive                      |                   |
| 23     | GND         | Ground and Signal Return for LVDS        |                   |
| 24     | RXIN3-      | LVDS Channel 3 negative                  |                   |
| 25     | RXIN3+      | LVDS Channel 3 positive                  |                   |
| 26     | GND         | Ground and Signal Return for LVDS        |                   |
| 27     | Reserved    | Open or High                             | AUO internal test |
| 28     | Reserved    | Open or High                             | AUO internal test |
| 29     | GND         | Ground and Signal Return                 |                   |
| 30     | GND         | Ground and Signal Return                 |                   |

**\*\* LVDS Option : Low/Open è NS (Normal)**


**High (3.3V) è JEIDA**



# LVDS Option = H (3.3V) è JEIDA



# LVDS Option = GND or OPEN è NS







## BACKLIGHT CONNECTOR PIN CONFIGURATION

### 1. Electrical specification

(Ta=25±5°C)

| No | ITEM                         | SYMBOL     | CONDITION                        | MIN           | TYP  | MAX  | UNIT      | Note             |
|----|------------------------------|------------|----------------------------------|---------------|------|------|-----------|------------------|
| 1  | Input Voltage                | $V_{DDB}$  | ---                              | 21.6          | 24.0 | 26.4 | $V_{DC}$  |                  |
| 2  | Input Current                | $I_{DDB}$  | $V_{DDB}=24V$<br>Max. Brightness | ---           | 3.0  | 3.4  | $A_{DC}$  | $V_{DIM}$ : Open |
| 3  | Input Power                  | $P_{DDB}$  | $V_{DDB}=24V$<br>Dimming Max.    | ---           | 72   | 81.6 | W         | $V_{DIM}$ : Open |
| 4  | Input inrush current, 0.3ms  | $I_{RUSH}$ | $V_{DDB}=24V$<br>Dimming Max.    | ---           | ---  | 3.4  | $A_{DC}$  | $V_{DIM}$ : Open |
| 5  | Output Frequency             | $F_{BL}$   | $V_{DDB}=24V$                    | ---           | 58   | ---  | kHz       |                  |
| 6  | ON/OFF Control Voltage       | $V_{BLON}$ | ON                               | $V_{DDB}=24V$ | 2.0  | 3.3  | $V_{DC}$  | or Open          |
|    |                              |            | OFF                              | $V_{DDB}=24V$ | 0.0  | ---  | $V_{DC}$  |                  |
| 7  | ON/OFF Control Current       | $I_{BLON}$ | $V_{DDB}=24V$                    | -1            | ---  | 1.5  | $mA_{DC}$ |                  |
| 8  | External PWM Control Voltage | $EV_{PWM}$ | MAX                              | ---           | 2.0  | 3.3  | $V_{DC}$  | or Open          |
|    |                              |            | MIN                              | ---           | -0.3 | ---  | $V_{DC}$  |                  |
| 9  | External PWM Control Current | $EI_{PWM}$ | MAX                              | PWM=100%      | 0.5  | ---  | $mA_{DC}$ |                  |
|    |                              |            | MIN                              | PWM=100%      | 0.5  | ---  | $mA_{DC}$ |                  |
| 10 | External PWM Duty Ratio      | $ED_{PWM}$ | ---                              | 30            | ---  | 100  | %         |                  |
| 11 | External PWM Frequency       | $EF_{PWM}$ | ---                              | 120           | 180  | 300  | Hz        |                  |

### 2. Input specification

CN1: S14B-PH-SM3-TB(JST) or Compatible

CN2: S2B-ZR-SM3A-TF(JST) or Compatible

CN3~10: SM02(12)B-BHS-1-TB(JST) or Compatible


| Pin No | Symbol    | Description                                 | Default |
|--------|-----------|---------------------------------------------|---------|
| 1      | VIN       | Operating Voltage Supply, +24V DC regulated | 24V     |
| 2      | VIN       | Operating Voltage Supply, +24V DC regulated | 24V     |
| 3      | VIN       | Operating Voltage Supply, +24V DC regulated | 24V     |
| 4      | VIN       | Operating Voltage Supply, +24V DC regulated | 24V     |
| 5      | VIN       | Operating Voltage Supply, +24V DC regulated | 24V     |
| 6      | GND       | Ground                                      | GND     |
| 7      | GND       | Ground                                      | GND     |
| 8      | GND       | Ground                                      | GND     |
| 9      | GND       | Ground                                      | GND     |
| 10     | GND       | Ground                                      | GND     |
| 11     | Reserved  | N.C.*                                       | -       |
| 12     | BL ON/OFF | On/Off Control                              | -       |
| 13     | PWM DIM   | External PWM Dimming Control                | -       |
| 14     | Reserved  | N.C.**                                      | -       |

\*: Pin11 and Pin14 are floating

\*\* : Pin14 setting can use GND or 3.3V and w/o any function problem

### 3. Backlight Diagram

**HOT: High Voltage**





### 3-3 Signal Timing Specifications

This is the signal timing required at the input of the User connector. All of the interface signal timing should be satisfied with the following specifications for it's proper operation.


\* Timing Table  
DE only Mode

|                     |           |           | Function ok |      |      | Recommend for Waterfall |             |      |
|---------------------|-----------|-----------|-------------|------|------|-------------------------|-------------|------|
| Signal              | Item      | Symbol    | Min         | Type | Max  | 50Hz                    | 60Hz        | Unit |
| Vertical Section    | Period    | Tv        | 784         | —    | 1015 | 789~822                 | 789~822     | Th   |
|                     | Active    | Tdisp (v) | 768         |      |      | 768                     |             | Th   |
|                     | Blanking  | Tblk (v)  | 16          | —    | 247  | 21~54                   | 21~54       | Th   |
| Horizontal Section  | Period    | Th        | 1414        | —    | 2000 | 1414~1722               | 1414~1722   | Tclk |
|                     | Active    | Tdisp (h) | 1366        |      |      | 1366                    |             | Tclk |
|                     | Blanking  | Tblk (h)  | 48          | —    | 634  | 48~356                  | 48~356      | Tclk |
| Clock               | Period    | CLK       |             | —    |      |                         | 18.18       | ns   |
|                     | Frequency | Freq      | 55          | —    | 88   | 55~88                   | 55~88       | MHz  |
| Vertical Frequency  | Frequency | Vs        | 44          |      | 66   | 48~52                   | 58~62       | Hz   |
| Horizntal Frequency | Frequency | Hs        | 39.45       |      | 53   | 39.45~41.1              | 47.34~49.32 | KHz  |

- \*1) DCLK signal input must be valid while power supply is applied.
- \*2) Display position is specific by the rise of DE signal only.  
Horizontal display position is specified by the falling edge of 1<sup>st</sup> DCLK right after the rise of DE, is displayed on the left edge of the screen.  
Vertical display position is specified by the rise of DE after a “Low” level period equivalent to eight times of horizontal period. The 1<sup>st</sup> data corresponding to one horizontal line after the rise of DE is displayed at the top line of screen.
- \*3.) If a period of DE “High” is less than 1366 DCLK or less than 768 lines, the rest of the screen displays black.
- \*4.) The display position does not fit to the screen if a period of DE “High” and the effective data period do not synchronize with each other.



3-4 Signal Timing Waveforms






### 3-5 Color Input Data Reference

The brightness of each primary color (red, green and blue) is based on the 8 bit gray scale data input for the color; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

#### COLOR DATA REFERENCE

| Color       |            | Input Color Data |    |    |    |     |    |    |    |       |    |    |    |     |    |    |    |      |    |    |    |     |    |    |    |   |  |  |  |
|-------------|------------|------------------|----|----|----|-----|----|----|----|-------|----|----|----|-----|----|----|----|------|----|----|----|-----|----|----|----|---|--|--|--|
|             |            | RED              |    |    |    |     |    |    |    | GREEN |    |    |    |     |    |    |    | BLUE |    |    |    |     |    |    |    |   |  |  |  |
|             |            | MSB              |    |    |    | LSB |    |    |    | MSB   |    |    |    | LSB |    |    |    | MSB  |    |    |    | LSB |    |    |    |   |  |  |  |
|             |            | R7               | R6 | R5 | R4 | R3  | R2 | R1 | R0 | G7    | G6 | G5 | G4 | G3  | G2 | G1 | G0 | B7   | B6 | B5 | B4 | B3  | B2 | B1 | B0 |   |  |  |  |
| Basic Color | Black      | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | Red(255)   | 1                | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | Green(255) | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | Blue(255)  | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1 |  |  |  |
|             | Cyan       | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1    | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1 |  |  |  |
|             | Magenta    | 1                | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1 |  |  |  |
|             | Yellow     | 1                | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1     | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | White      | 1                | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1     | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1    | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1 |  |  |  |
| RED         | RED(000)   | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | RED(001)   | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 1  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | ----       |                  |    |    |    |     |    |    |    |       |    |    |    |     |    |    |    |      |    |    |    |     |    |    |    |   |  |  |  |
|             | RED(254)   | 1                | 1  | 1  | 1  | 1   | 1  | 1  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | RED(255)   | 1                | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
| GREEN       | GREEN(000) | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | GREEN(001) | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 1  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | ----       |                  |    |    |    |     |    |    |    |       |    |    |    |     |    |    |    |      |    |    |    |     |    |    |    |   |  |  |  |
|             | GREEN(254) | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1   | 1  | 1  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | GREEN(255) | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
| BLUE        | BLUE(000)  | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0 |  |  |  |
|             | BLUE(001)  | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0   | 0  | 0  | 1  |   |  |  |  |
|             | -----      |                  |    |    |    |     |    |    |    |       |    |    |    |     |    |    |    |      |    |    |    |     |    |    |    |   |  |  |  |
|             | BLUE(254)  | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0 |  |  |  |
|             | BLUE(255)  | 0                | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1 |  |  |  |

### 3-6 Power Sequence



| Parameter | Values         |      |      | Units |
|-----------|----------------|------|------|-------|
|           | Min.           | Typ. | Max. |       |
| t1        | 470            | -    | 1000 | us    |
| t2        | 20             | -    | 50   | ms    |
| t3        | 700 or (200)*1 | -    | -    | ms    |
| t4        | 200            | -    | -    | ms    |
| t5        | 50             | -    | -    | ms    |
| t6        | 0.47           | -    | 30   | ms    |
| t7        | 1              | -    | -    | s     |

\*1: If t3=200ms, input black signal till 700ms from system is necessary.

In case of t3<200ms, the abnormal display will be happened. But it will not damage timing controller.


Note:

The timing controller will not be damaged in case of TV set AC input power suddenly shut down. Once power reset, it should follow power sequence as spec. definition.

- (1) Apply the lamp voltage within the LCD operation range. When the back-light turns on before the LCD operation or the LCD turns off before the back-light turns off, the display may momentarily become abnormal screen.



# Power Sequence for Inverter




| Parameter | Values |      |      | Units |
|-----------|--------|------|------|-------|
|           | Min.   | Typ. | Max. |       |
| T1        | 20     | -    | -    | ms    |
| T2        | 500    | -    | -    | ms    |
| T3        | 0      | -    | -    | ms    |
| T4        | 1      | -    | -    | ms    |
| T5        | -      | -    | 10   | ms    |

## 4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 45 minutes in a dark environment at 25°C. The values specified are at an approximate distance 50cm from the LCD surface at a viewing angle of  $\Phi$  and  $\theta$  equal to 0°.

Fig.1 1 presents additional information concerning the measurement equipment and method.



| Parameter                |                                | Symbol                      | Values     |       |           | Units             | Notes |
|--------------------------|--------------------------------|-----------------------------|------------|-------|-----------|-------------------|-------|
|                          |                                |                             | Min.       | Typ.  | Max.      |                   |       |
| Contrast Ratio           |                                | CR                          | 500        | 600   |           |                   | 1     |
| Dark Luminance           |                                | LBK                         |            |       | 1.0       | cd/m <sup>2</sup> | 2     |
| Surface Luminance, white |                                | LWH                         | 400        | 500   |           | cd/m <sup>2</sup> | 2     |
| Luminance Variation      |                                | $\delta_{\text{WHITE}}$ 5 p |            |       | 1.3       |                   | 3     |
| Response Time            | Rise Time                      | Tr <sub>R</sub>             |            | 15    |           | ms                | 4     |
|                          | Decay Time                     | Tr <sub>D</sub>             |            | 5     |           |                   |       |
|                          |                                | Gray to Gray                | T $\gamma$ |       | 8         |                   | ms    |
| Color Coordinates        |                                |                             |            |       |           |                   |       |
|                          | RED                            | R <sub>X</sub>              | Typ.-0.03  | 0.640 | Typ.+0.03 |                   |       |
|                          |                                | R <sub>Y</sub>              |            | 0.330 |           |                   |       |
|                          | GREEN                          | G <sub>X</sub>              |            | 0.270 |           |                   |       |
|                          |                                | G <sub>Y</sub>              |            | 0.600 |           |                   |       |
|                          | BLUE                           | B <sub>X</sub>              |            | 0.150 |           |                   |       |
|                          |                                | B <sub>Y</sub>              |            | 0.060 |           |                   |       |
|                          | WHITE                          | W <sub>X</sub>              |            | 0.280 |           |                   |       |
|                          |                                | W <sub>Y</sub>              |            | 0.290 |           |                   |       |
| Viewing Angle            |                                |                             |            |       |           |                   |       |
|                          | x axis, right( $\varphi$ =0°)  | $\theta_{\text{r}}$         |            | 88    |           | Degree            | 6     |
|                          | x axis, left( $\varphi$ =180°) | $\theta_{\text{l}}$         |            | 88    |           | Degree            |       |
|                          | y axis, up( $\varphi$ =90°)    | $\theta_{\text{u}}$         |            | 88    |           | Degree            |       |
|                          | y axis, down ( $\varphi$ =0°)  | $\theta_{\text{d}}$         |            | 88    |           | Degree            |       |



Note:

1. Contrast Ratio (CR) is defined mathematically as:

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance of } L_{\text{on1}}}{\text{Surface Luminance of } L_{\text{off1}}}$$

2. Surface luminance is luminance value at point 1 across the LCD surface 50cm from the surface with all pixels displaying white. From more information see FIG 2. When  $V_{\text{DDB}} = 24\text{V}$ ,  $I_{\text{DDB}} = 3.5\text{A}$ .  $L_{\text{WH}} = L_{\text{on1}}$

Where  $L_{\text{on1}}$  is the luminance with all pixels displaying white at center 1 location.

3. The variation in surface luminance,  $\delta_{\text{WHITE}}$  is defined (center of Screen) as:


$$\delta_{\text{WHITE(5P)}} = \frac{\text{Maximum}(L_{\text{on1}}, L_{\text{on2}}, \dots, L_{\text{on5}})}{\text{Minimum}(L_{\text{on1}}, L_{\text{on2}}, \dots, L_{\text{on5}})}$$

4. Response time is the time required for the display to transition from black to white(Rise Time,  $\text{Tr}_\text{R}$ ) and from white to black (Decay Time,  $\text{Tr}_\text{D}$ ). For additional information see FIG3.

5.  $T_\gamma$  is the response time between any two gray scale and is based on  $f_v = 60\text{Hz}$  to optimize.


6. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG4.

**FIG. 2 Luminance**




**FIG.3 Response Time**

The response time is defined as the following figure and shall be measured by switching the input signal for “black” and “white”.



**FIG.4 Viewing angle**






## 5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model T260XW02. In addition the figures in the next page are detailed mechanical drawing of the LCD.

|                     |                           |                                        |
|---------------------|---------------------------|----------------------------------------|
| Outline Dimension   | Horizontal                | 626.0mm                                |
|                     | Vertical                  | 373.0mm                                |
|                     | Depth                     | 43.3mm(w/i mylar inverter & Shielding) |
| Bezel Area          | Horizontal                | 580.8mm                                |
|                     | Vertical                  | 328.8mm                                |
| Active Display Area | Horizontal                | 575.769mm                              |
|                     | Vertical                  | 323.712mm                              |
| Weight              | 4200g (Typ.)              |                                        |
| Surface Treatment   | Anti-Glare (3H), Haze=40% |                                        |

# Front View





## 6. Reliability

Environment test condition

| No | Test Item                         | Condition                                                                                                                     |
|----|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| 1  | High temperature storage test     | Ta=60°C 240h                                                                                                                  |
| 2  | Low temperature storage test      | Ta=-20°C 240h                                                                                                                 |
| 3  | High temperature operation test   | Ta=50°C 80%RH 240h                                                                                                            |
| 4  | Low temperature operation test    | Ta=0°C 240h                                                                                                                   |
| 5  | Vibration test<br>(non-operating) | Wave form: random<br>Vibration level : 1.0G RMS<br>Bandwidth : 10-500Hz<br>Duration: X, Y, Z 20min<br>One time each direction |
| 6  | Shock test<br>(non-operating)     | Shock level: 100G<br>Waveform: half sine wave, 2ms<br>Direction: $\pm X$ , $\pm Y$ , $\pm Z$<br>One time each direction       |
| 7  | Vibration test<br>(with carton)   | Random Vibration:10~200Hz,1.5G,30minutes<br>in each X,Y,Z direction                                                           |
| 8  | Drop test<br>(with carton)        | Height: 53.3cm<br>1 corner, 3 edges, 6 surfaces<br>(ASTMD4169-I)                                                              |
| 9  | Altitude<br>Storage/shipment      | 50,000 feet (12Kpa)                                                                                                           |

{ Result Evaluation Criteria }

There should be no change which might affect the practical display function when the display quality test is conducted under normal operating condition.





## 7. International Standard

### 7-1. Safety

- (1) UL1950 Third Edition, Underwriters Laboratories, Inc. Jan. 28, 1995  
Standard for Safety of Information Technology Equipment Including electrical Business Equipment.
- (2) CAN/CSA C22.2 No. 950-95 Third Edition, Canadian Standards Association, Jan. 28, 1995  
Standard for Safety of Information Technology Equipment Including Electrical Business Equipment.
- (3) EN60950 : 1992+A2: 1993+A2: 1993+C3: 1995+A4: 1997+A11: 1997  
IEC 950: 1991+A1: 1992+A2: 1993+C3: 1995+A4:1996  
European Committee for Electrotechnical Standardization (CENELEC)  
EUROPEAN STANDARD for Safety of Information Technology Equipment Including Electrical Business Equipment.

### 7-2. EMC

- a) ANSI C63.4 “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electrical Equipment in the Range of 9kHz to 40GHz. “American National standards Institute(ANSI), 1992.
- b) C.I.S.P.R “Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment.” International Special committee on Radio Interference.
- c) EN 55022 “Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment.” European Committee for Electrotechnical Standardization. (CENELEC), 1998.





8. Packing

Label sample    83mm \* 23mm




Carton Label





Carton Size 767(L)mm\*330(W)mm\*480(H)mm





## 9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

### 9-1 MOUNTING PRECAUTIONS

- (1) You must mount a module using holes arranged in four corners or four sides.
- (2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- (3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to resist external force.
- (4) You should adopt radiation structure to satisfy the temperature specification.
- (5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- (6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth. (Some cosmetics are detrimental to the polarizer.)
- (7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front/ rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
- (8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (9) Do not open the case because inside circuits do not have sufficient strength.

### 9-2 OPERATING PRECAUTIONS

- (1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage:  $V = \pm 200\text{mV}$  (Over and under shoot voltage)
- (2) Response time depends on the temperature. (In lower temperature, it becomes longer..)
- (3) Brightness depends on the temperature. (In lower temperature, it becomes lower.) And in lower temperature, response time (required time that brightness is stable after turned on) becomes longer.
- (4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
- (6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interface.



### **9-3 ELECTROSTATIC DISCHARGE CONTROL**

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

### **9-4 PRECAUTIONS FOR STRONG LIGHT EXPOSURE**

Strong light exposure causes degradation of polarizer and color filter.

### **9-5 STORAGE**

When storing modules as spares for a long time, the following precautions are necessary.

- (1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
- (2) The polarizer surface should not come in contact with any other object. It is recommended that they be stored in the container in which they were shipped.

### **9-6 HANDLING PRECAUTIONS FOR PROTECTION FILM**

- (1) The protection film is attached to the bezel with a small masking tape. When the protection film is peeled off, static electricity is generated between the film and polarizer. This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
- (2) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the Bezel after the protection film is peeled off.
- (3) You can remove the glue easily. When the glue remains on the Bezel or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.